# Synology



# DiskStation DS3615xs

Synology DiskStation DS3615xs provides the reliable and ultra-high performance network attached storage solution for large scale businesses that require an efficient way to centralize data protection, simplify data management, deploy virtualization solutions, and rapidly expand storage capacity with minimal time spent on setup and maintenance. Synology DS3615xs is backed with Synology's 5-year limited warranty.

# **Highlights**

- Ultra-high performance of 2,352 MB/s sequential read throughput and 268,064 sequential read IOPS<sup>1</sup>
- Scale up to 36 drives with Synology DX1215<sup>2</sup>
- One PCIe slot to support high
  performance network interface
  card
- Expandable ECC RAM module (up to 32GB)
- SATA III 6Gb/s interface support
- High Availability and SSD read/write cache supportt
- Backed with next business day replacement service<sup>3</sup>
- VMware<sup>®</sup>, Citrix<sup>®</sup>, and Microsoft<sup>®</sup> Hyper-V<sup>®</sup> certified
- Running on Synology DiskStation Manager (DSM)

## **Ultra-High Performance**

DS3615xs delivers ultra-high performance at **2,352 MB/s sequential read throughput** and **268,064 sequential read IOPS** under RAID 5 configuration with VLAN<sup>1</sup>. Through advanced flash technology, the combination of hard drives and **read/writeoptimized SSD cache** boosts throughput efficiently while minimizing cost per gigabyte. In addition, DS3615xs comes with **native SATA III 6Gb/s support** that unleashes the full potential of blazing fast SSDs, ensuring the optimum data process under heavy system loading.

In addition to default 4 Gigabit ports, DS3615xs comes with one **PCIe 3.0 x8 slot**, allowing installation of one high performance Network Interface Card (NIC) for maximized bandwidth, bringing you the superior performance that data-intensive applications demand of your storage system.

Equipped with 4GB RAM and **up to 32GB** ECC RAM expansion support, DS3615xs ensures data accuracy as well as ultra-high performance to provide a rigorous foundation for the mission-critical tasks of your business.

## **Robust Scalability**

When the storage capacity of DS3615xs nears its limit, expansion is easily accomplished with **Synology DX1215** via specially-designed connection cables to maximize data transmission throughput between main server and expansion units. With two DX1215 attached, DS3615xs supports up to **36 drives** and **216TB** of raw capacity<sup>2</sup> and provides the ability to seamlessly expand a single volume up to 108TB on the fly.

Management of the large storage space on DS3615xs is simple and flexible. Multiple Volumes on RAID allows users to create more than one volume on a RAID structure, providing a flexible and efficient way to manage the storage across all hard drives. When the need for more space arises, the volume could be easily expanded without any service disruption.



# Figure 1) Reliability, Availability & Disaster Recovery

High Availability Manager ensures seamless transition between clustered servers in the event of server failure with minimal impact to businesses.

## **Comprehensive Business Applications**

Powered by the innovative **Synology DiskStation Manager** (DSM), DS3615xs comes fully-equipped with applications and features designed specifically for large-scale business:

- Easy integration with existing business network environments through **Windows® AD** and **LDAP** directory services without recreating user accounts.
- Windows ACL support provides fine-grained access control and efficient privilege settings, allowing DS3615xs to fit seamlessly into current infrastructure.
- Built-in backup applications protect information assets by regularly backing up files and **iSCSI LUNs** locally and remotely.
- Continuous data protection with **snapshots** of shared folders allows restoration of previous versions when the need arises.

### Reliability, Availability & Disaster Recovery

System reliability is of paramount importance to businesses which depend upon their commercial servers every day. DS3615xs responds to these concerns with wide-ranging availability and redundancy features:

- **High Availability Manager** ensures seamless transition between clustered servers in the event of server failure with minimal impact to applications.
- Shared Folder Sync replicates data in real-time to another Synology NAS at a remote location for prompt disaster recovery to meet the Recovery Time Objective (RTO) of your business
- High reliability system design including **fan-less CPU heat-sink** and passive cooling technology prevents single point of failure.
- Equipped with two 120 X 120 mm fans and a smart airflow design to keep the system running cool 24/7, while its noise dampening design makes it much quieter than PC counterparts.
- ECC RAM modules detect and correct errors during data transmission.

### **Unified Storage System**

By integrating file-level (NAS) and block-level (SAN) storage into one unified storage system, DS3615xs enables businesses to cost-effectively manage multi-protocol data and reduce total cost of ownership:

- Comprehensive network protocol support (CIFS/SMB, AFP and NFS) ensures seamless file sharing across Windows, Mac<sup>®</sup>, and Linux<sup>®</sup> platforms.
- Affordable and cost-effective iSCSI allows large scale business to consolidate storage into data center storage arrays.
- Thin provisioning, available for file-level iSCSI LUN, maximizes storage utilization by enabling administrators to oversubscribe provision and grow storage space as needed. Thick provisioning further maximizes the performance of virtualization applications.

## Virtualization Certified

DS3615xs provides seamless storage solutions for virtualization environments, including VMware, Citrix, and Hyper-V. With VMware vSphere 5 and VAAI integration certified, DS3615xs helps offload specific storage operations and optimizes computation power for unparalleled performance and efficiency in VMware environments. As the centralized storage of a virtual environment, DS3615xs enables virtual machine migration, allowing movement from server to server whilst eliminating service downtime and disruption to user. Windows Offloaded Data Transfer (ODX) and Synology Advanced LUN support extremely improves the efficiency on massive data transfer and migration.

# **Connections & Buttons**



# **Technical Specifications**

Hardware

| 11a1 uwai c                   |   |
|-------------------------------|---|
| CPU                           | Intel Core i3-4130 Dual Core 3.4GHz   |
| Hardware Encryption Engine    | Yes (AES-NI)  |
| Floating Point                | Yes   |
| Memory                        | 4GB DDR3 ECC RAM (Expandable, up to 32GB)   |
| Internal HDD/SSD              | 3.5" or 2.5" SATA(III) / SATA(II) X 12 (hard drives not included)   |
| Maximum Internal Raw Capacity | 72TB (12 X 6TB HDD) (The actual capacity will differ according to volume types)   |
| External Ports                | USB 3.0 X 2, Expansion Port X 2   |
| Size (HxWxD)                  | 270 X 300 X 340 mm  |
| Weight                        | 9.8kg   |
| LAN                           | Gigabit X 4 (with 1 X PCIe slot to support high performance network interface card)   |
| Wake on LAN/WAN               | Yes   |
| Wireless Support (dongle)     | Yes   |
| AC Input Power Voltage        | 100V to 240V AC   |
| Power Frequency               | 50 / 60Hz, Single Phase   |
| Operating Temperature         | 5°C to 35°C (40°F to 95°F)  |
| Storage Temperature           | -20°C to 60°C (-5 to 140°F)   |
| Relative Humidity             | 5% to 95% RH  |
| General                       |   |
| Networking Protocols          | CIFS, AFP, NFS, FTP, WebDAV, CalDAV, iSCSI, Telnet, SSH, SNMP, VPN (PPTP, OpenVPN™, L2TP)   |
| File System                   | Internal: EXT4<br>External: EXT4, EXT3, FAT, NTFS, HFS+   |
| Storage Management            | Maximum File System Size: 108TB, Maximum Internal Volume #: 1024, Maximum iSCSI Target #: 64,<br>Maximum iSCSI LUN#: 512, RAID Clone/Snapshot support; Supported RAID Type : Basic, JBOD, RAID 0,<br>RAID 1, RAID 5, RAID 6, RAID 10; Synology Expansion Unit Support: DX1215 X 2 |
| File Sharing Capability       | Maximum User Account: 16000, Maximum Group: 512, Maximum Shared Folder: 512, Maximum<br>Concurrent CIFS/AFP/FTP Connections : 1024  |
| Privilege                     | Windows Access Control List (ACL)   |
| Virtualization                | VMware vSphere 5, Microsoft Hyper-V, Citrix Certified   |
| Directory Service             | Windows AD Integration: Domain Users login via Samba (CIFS)/AFP/FTP/File Station, LDAP Integration  |
| Security                      | FTP over SSL/TLS, IP Auto-Block, Firewall, Encrypted Network Backup over Rsync, HTTPS Connection  |
| Utilities                     | Synology Assistant, Cloud Station, Evidence Integrity Authenticator   |
| Supported Clients             | Windows XP onward, Mac OS X® 10.5 onward, Ubuntu 9.04 onward  |
| Supported Browsers            | Chrome®, Firefox® Internet Explorer®: 8 or later, Safari® 5 or later, Safari (iOS 5 or later on iPad®), Chrome<br>(Android™ 4.0 on tablets)   |
| Language                      | English, Deutsch, Français, Italiano, Español, Dansk, Norsk, Svensk, Nederlands, Русский, Polski, Magyar,<br>Português do Brasil, Português Europeu, Türkçe, Český, 日本語, 한국어, 繁體中文, 简体中文  |

### **Applications**

| File Station               | Virtual Drive, Remote Folder  |
|----------------------------|---|
| Backup Solutions           | Network Backup, Local Backup, Desktop Backup, Shared Folder Sync - Maximum Task Number: 16,<br>Configuration Backup   |
| Mail Server                | Supported Mail Server Protocols: POP3, SMTP, IMAP   |
| FTP Server                 | Bandwidth Control, Custom FTP Passive Port Range, Anonymous FTP, Transfer Log   |
| Web Station                | Virtual Host (up to 30 websites), PHP/MySQL®, 3rd-Party Applications Support  |
| Printer Server             | Maximum Printer #: 2, Printing Protocols: LPR, CIFS, IPP, Apple iOS Printing, Google Cloud Print™, Multi<br>Functional Print Server (MFP functions are for Windows PC only) |
| Log Center                 | SSL Connection, Log Rotation: 6 months, 1 year, 2 years, 3 years, Email Notification  |
| iOS/Android Applications   | DS audio, DS cam, DS cloud, DS download, DS file, DS finder, DS photo+, DS video, DS note   |
| Windows Phone Applications | DS audio, DS download, DS file, DS finder, DS photo+, DS video  |

### **Add-on Packages**

| Surveillance Station | Default IP cam #: 2, Maximum IP cam # (licenses required): 75 (with two free licenses to install two IP cameras. Additional licenses can be purchased to expand the license quota.) |
|----------------------|---|
| VPN Server           | Maximum Connections: 30, VPN Method: PPTP, OpenVPN, L2TP  |
| Mail Station         | Webmail Interface for Mail Server, Receiving Mails from Multiple POP3 Mailboxes, Customizable SMTP<br>Server  |
| Antivirus Essential  | Full System Scan, Scheduled Scan, White List Customization, Virus Definition Auto Update  |
| Time Backup          | Maximum Task Number: 16, Multiple File Versions Retained, Instant File Restoration  |
| Cloud Station        | Maximum Concurrent File Transfers: 1024, Retain Historical and Deleted File Versions  |
| Cloud Sync           | Data Sync with Public Cloud Services: Dropbox, Google Drive, Baidu, Microsoft OneDrive, Box and<br>hubiC  |
| Download Station     | Supported Download Protocols: BT/HTTP/FTP/NZB/eMule<br>Maximum Concurrent Download Tasks : 80   |
| Other Packages       | Photo Station, Audio Station, iTunes® Server, 3rd-party packages  |

### **Environment and Packaging**

| Environment          | RoHS Compliant   |
|----------------------|--|
| Package Content      | DS3615xs Main Unit, Welcome Note, Accessory Pack, AC Power Cord, RJ-45 LAN Cable X 2           |
| Optional Accessories | Remote, Camera License Pack, 4GB, 8GB and 16GB ECC RAM Module Kit, Expansion Unit (DX1215 X 2) |
| Warranty             | 5 years  |

\*Model specifications are subject to change without notice. Please refer to www.synology.com for the latest information.

1. Performance may vary depending on the environment.

2.DS3615xs supports up to two Synology DX1215, purchased separately.

3. Available in selected countries only. For detailed terms and conditions, please visit the Synology Replacement Service (SRS) website at https://srs.synology.com.

### SYNOLOGY INC.

Synology is dedicated to taking full advantage of the latest technologies to bring businesses and home users reliable and affordable ways to centralize data storage, simplify data backup, share and sync files across different platforms, and access data on-the-go. Synology aims to deliver products with forward-thinking features and the best in class customer services.

Copyright © 2014, Synology Inc. All rights reserved. Synology, the Synology logo are trademarks or registered trademarks of Synology Inc. Other product and company names mentioned herein may be trademarks of their respective companies. Synology may make changes to specification and product descriptions at anytime, without notice. Printed in Taiwan.

DS3615xs-2014-ENU-REV002

#### Headquarters

Synology Inc. 3F-3, No. 106, Chang An W. Rd., Taipei, Taiwan Tel: +886 2 2552 1814 Fax: +886 2 2552 1824

Synology France SARL

39 rue Louis Blanc,

92400 Courbevoie

Tel: +33 147 176288

France

France

### China

Synology Shanghai 20070, Room 516, No. 638, Hengfeng Rd., Zhabei Dist., Shanghai

### North & South America

Synology America Corp. 13343 NE Bel-Red Road, Bellevue, WA 98005 USA Tel: +1 425 818 1587

### **United Kingdom**

Synology UK Ltd. Unit C, Denbigh West Business Park, Third Avenue, Bletchley, Milton Keynes, MK1 10H, UK Tel: +44 1908 366380

### Germany

Synology GmbH Grafenberger Allee 125 40237 Düsseldorf Deutschland Tel: +49 211 9666 9666